



## Extreema® corner protection

Made from 100% Dyneema®

- Highest abrasion resistance of any fiber
- Excellent dynamic toughness
- Very low elongation
- Excellent flex fatigue resistance
- Superior cut resistance
- Exceptional flexibility
- Superior tear resistance
- Significantly longer life-time of round slings and webbing slings
- Easy to put on, easy to take of equipped with Velcro
- It's always in the right place; Easy to place on the anchoring points, or the most vulnerable place



Available sizes, use and prices:

Type	Suitable for Round sling load capacity	Suitable for Lifting sling webbing width	Dimensions		
			Width	Length	Thickness
EXCP/85/500*	1T-6T	up to 75mm	85mm	500mm	12mm
EXCP/115/500*	8T	up to 100mm	115mm	500mm	12mm
EXCP/135/500*	10T-12T	up to 120mm	135mm	500mm	12mm
EXCP/160/500*	15T	up to 150mm	160mm	500mm	12mm
EXCP/190/600	20T-25T	up to 180mm	190mm	600mm	12mm
EXCP/230/800	30T-40T	up to 200mm	230mm	800mm	12mm
EXCP/260/800	45T	up to 240mm	260mm	800mm	12mm
EXCP/290/800	50T-55T	up to 240mm	290mm	800mm	12mm

\*minimum order quantity is 2

“There are no limits in using quality products for safer lifting jobs”

